

## **BACKLIGHT SPRAY SOLL (S700016)**

**Product information** 

Page 1/1

Turn the can around after use and spray the valve until it is empty.
Red
150 ml
Protect from sunlight and do not expose to temperature exceeding +50°C. We guarantee shelf life and quality of the product not less than 3 years.
lacquers necessary.
No pre-treatment with primers and no follow-up treatment with other top coats or clear
With itself: at any time.
Completely dry: after approx. 12 hours.
Dust dry: after approx. 20 minutes.
For 2 cross-coats: approx. 40 - 50 µm.
Nitro combination resins.
Very weather resistant.
Scratch resistant.
Good drying properties.
Rapid tack-drying.
High level of solid matter.
Very economic.
Very easy running.
Varnishing, top quality special product.
· Observe the note and instructions on the can label.
· Do not spray on surfaces coated with synthetic resins as the paint may lift.
· Not permitted within the scope of the road traffic regulations!
after approx. 20 minutes, thoroughly dry after 12 hours.
tone. Spray crosswise in thin layers. Spraying distance approx. 25 cm. Touch-dr
down. Shake can for at least 2 minutes. Test spray to check compatibility and color
ceramics etc. Before usage, clean the surface thoroughly, remove rust and sand
wind deflectors, glass panes, glass, metal, wood objects, lamps, neon lights

This data sheet is for information purpose only. To our knowledge the data provided complies with the latest standard and is based on years of experience in the manufacture of our products. However the data is not binding and without warranty.